



MEDUSA

Turnable
Linear Wall-Washer
Series



Modular Adjustable
Design



Adjustable
Tilt



Anti-Glare
Options

MEDUSA

Turnable Linear Wall-Washer

Medusa

(Standard)



IP66	DMX	1-10V	DALI
2-3step McAdam <small>(optional)</small>	Driver Included	Operating Hours > 100,000	L70 > 50,000 Hours
CRI 80 90 90+	OPERATION TEMP -20°C to 50°C!	5 Years warranty	RoHS CE

SPECIFICATIONS

Product Code	LED Output (lm)	LED Power	Efficiency (lm/W)	Max. Length	IP Rating	Input Voltage
LY-LD-MDS-6W-①-②-③-④	600	6	100	Up to 6 Modules	66	24Vdc

CUSTOMIZABLE SPECIFICATIONS

① Beam Angle	② Colour Temperature	③ Housing Colour	④ Dimming
10D 15D 25D 30D 40D 60D	1030D (10° x 30°) 1065D (10° x 65°) 2065D (20° x 65°)	27 (2700K) 30 (3000K) 40 (4000K) 50 (5000K)	WH (White) BK (Black)
			ND (Non-Dimming) DA (Dali) D0 (0-10V) DMX (512DMX)

(Example Code Format: LY-LD-MDS-6W-10D-30-27-WH-NA)

DIMENSIONS (MM) & LIGHT DISTRIBUTION

(10D)

(15D)

(25D)

(30D)

(40D)

(60D)

(1030D)

(1065D)

(2065D)

Technical drawing showing dimensions: 40, 79, 76, 166, 170, 56, ø6.5

MEDUSA

Turnable Linear Wall-Washer

Medusa Anti-Glare

(Symmetrical)



IP66	DMX	1-10V	DALI
2-3step McAdam <small>(optional)</small>	Driver Included	Operating Hours > 100,000	L70 > 50,000 Hours
CRI 80 90 90+	OPERATION TEMP -20°C to 50°C!	5 Years warranty	RoHS
			CE

SPECIFICATIONS

Product Code	LED Output (lm)	LED Power	Efficiency (lm/W)	Max. Length	IP Rating	Input Voltage
LY-LD-MDSY-6W-①-②-③-④	600	6	100	Up to 6 Modules	66	24Vdc

CUSTOMIZABLE SPECIFICATIONS

① Beam Angle	② Colour Temperature	③ Housing Colour	④ Dimming
10D 15D 25D 30D 40D 60D	1030D (10° x 30°) 1065D (10° x 65°) 2065D (20° x 65°)	27 (2700K) 30 (3000K) 40 (4000K) 50 (5000K)	WH (White) BK (Black)
			ND (Non-Dimming) DA (Dali) D0 (0-10V) DMX (512DMX)

(Example Code Format: LY-LD-MDSY-6W-10D-30-27-WH-NA)

DIMENSIONS (MM) & LIGHT DISTRIBUTION

(10D)

(15D)

(25D)

(30D)

(40D)

(60D)

(1030D)

(1065D)

(2065D)

MEDUSA

Turnable Linear Wall-Washer

Medusa Anti-Glare

(Asymmetrical)



IP66	DMX	1-10V	DALI
2-3step McAdam <small>(optional)</small>	Driver Included	Operating Hours > 100,000	L70 > 50,000 Hours
CRI 80 90 90+	OPERATION TEMP -20°C to 50°C!	5 Years warranty	RoHS CE

SPECIFICATIONS

Product Code	LED Output (lm)	LED Power	Efficiency (lm/W)	Max. Length	IP Rating	Input Voltage
LY-LD-MDAY-6W-①-②-③-④	600	6	100	Up to 6 Modules	66	24Vdc

CUSTOMIZABLE SPECIFICATIONS

① Beam Angle	② Colour Temperature	③ Housing Colour	④ Dimming
10D 15D 25D 30D 40D 60D	1030D (10° x 30°) 1065D (10° x 65°) 2065D (20° x 65°)	27 (2700K) 30 (3000K) 40 (4000K) 50 (5000K)	WH (White) BK (Black)
			ND (Non-Dimming) DA (Dali) D0 (0-10V) DMX (512DMX)

(Example Code Format: LY-LD-MDAY-6W-10D-30-27-WH-NA)

DIMENSIONS (MM) & LIGHT DISTRIBUTION

(10D)

(15D)

(25D)

(30D)

(40D)

(60D)

(1030D)

(1065D)

(2065D)

40
66
76

166
170

56
ø6.5